

This is a low voltage (24VDC) fixture and must be wired with the included 24VDC driver(s). Drivers are not integral to the fixture. Learn more at lukelampco.com/drivers.

Canopy Detail

Fixture Details

Dimensions

18in H x 1in W x 1in D
Canopy Diameter: 2.25in
Weight: ~2 pounds

Mounting

Mounts directly to hollow ceiling. Pendant cord is field-adjustable from 6in to 120in, and up to 300in upon request. For mounting to junction boxes, please contact sales.

Light Output

137 lumens delivered. Decorative only, not a primary light source.
4W @ 24VDC

Lamping

Dimmable 24VDC integral LED.
95+ CRI. 50,000+ hour lifespan.

Cord Length

120in of field-adjustable pendant cord provided. To request a custom length up to 300in, specify below.

Finish

Satin Brass, Blackened Brass, Antique Brass, Satin Nickel, Polished Nickel, & Satin Copper.
More at lukelampco.com/finishes.


Color Temperature

1800K, 2000K, 2400K, 2700K, 3000K, 3500K, 4200K, & 5000K.

Driver

One 24VDC LED driver required.
Fixture must be installed with the included driver. Driver is not integral to the fixture.
More at lukelampco.com/drivers.

Dimensions



Specifying Code

Fixture Code	Cord Length	Finish	Color Temperature	Driver	Certification
1.5FT - RE - P	—	—	—	—	For indoor use only.



Scan QR code to view instruction manual

—IN - 120in of field-adjustable cord included. If more is needed, up to 300in can be specified here.

SB - Satin Brass
BB - Blackened Brass
AB - Antique Brass
SN - Satin Nickel
PN - Polished Nickel
SC - Satin Copper

18 - 1800K
20 - 2000K
24 - 2400K
27 - 2700K
30 - 3000K
35 - 3500K
42 - 4200K
50 - 5000K



UNI - Universal Remote MLV/ELV/010V (120-277V)
SW - Switchex (120V)

For more info, visit lukelampco.com/drivers

DR - UL Dry (Indoor)
DM - UL Damp (Indoor)
CR - CE Dry (Indoor)*
CM - CE Damp (Indoor)*

* If CE is specified, we cannot supply the drivers.