

# **FIXTURE DETAILS**

## Dimensions

Overall: 144in L x 27in H Weight: ~23 pounds Canopy Diameter: 5 inches

## Mounting

Two junction boxes (120" on center) with a central aircraft cable for additional support. Both junction boxes require power. Two remotely mounted 24VDC drivers required.

## Light Output

4320 lumens delivered. Decorative only, not a primary light source. 112 watts @ 24VDC.

## Lamping

Dimmable 24VDC integral LED. 95+ CRI. 50,000+ hour lifespan.

# Cord / Cable Length

120in of field-adjustable pendant cord and aircraft cable provided. To request a custom length up to 300in, specify below.

#### Finish

Satin brass, blackened brass, antique brass, satin nickel, polished nickel, & satin copper. For more information visit lukelampco.com/finishes.

## **Color Temperature**

1800K, 2000K, 2400K, 2700K, 3000K, 3500K, 4200K, & 5000K.

## Driver

Must be installed with the included 24VDC driver(s). Driver(s) are not integral to the fixture. For more info visit lukelampco.com/drivers.

# **TERMS EXPLAINED**



## SPECIFYING CODE

FIXTURE CODE	CORD / CABLE LENGTH	FINISH	COLOR TEMPERATURE	DRIVER	CERTIFICATION
12FT - TB1 - FELR		-	-	_ UNI	For indoor use only.
	<b>IN</b> - 120in of field- adjustable cord/cable included. If more is needed, up to 300in can be specified here.	SB - Satin Brass BB - Blackened Brass AB - Antique Brass SN - Satin Nickel PN - Polished Nickel	18 - 1800K 20 - 2000K 24 - 2400K 27 - 2700K 30 - 3000K	<b>UNI</b> - Universal Remote MLV/ELV/010V (120-277V) For more info, visit lukelampco.com/drivers	DR - UL Dry (Indoor) DM - UL Damp (Indoor) CR - CE Dry (Indoor)* CM - CE Damp (Indoor)*
Scan QR code to view instruction manual		SC - Satin Copper	<b>35</b> - 3500K <b>42</b> - 4200K <b>50</b> - 5000K		* If CE is specified, we cannot supply the drivers.