

FIXTURE DETAILS

Dimensions

Overall: 30in H x 12in W x 2in D
Weight: ~10 pounds
Shield Diameter: 6.5 inches

Mounting

Fixture can mount directly to a hollow wall (toggle bolts included). Two mounting points 18" apart on center. Adapter plate included for optional j-box mounting.

Light Output

413 lumens delivered. Decorative only, not a primary light source. 11 watts @ 24VDC.

Lamping

Dimmable 24VDC integral LED. 95+ CRI. 50,000+ hour lifespan.

Orientation

Left or Right (see above) styled at installation.

ADA Compliance

This fixture is ADA Compliant.

Finish

Satin Brass, Blackened Brass, Antique Brass, Satin Nickel, Polished Nickel, & Satin Copper. For more information visit [lukelampco.com/finishes](https://www.lukelampco.com/finishes).


Color Temperature

1800K, 2000K, 2400K, 2700K, 3000K, 3500K, 4200K, & 5000K.


Driver

Must be installed with the included 24VDC driver(s). Driver(s) are not integral to the fixture. For more info visit [lukelampco.com/drivers](https://www.lukelampco.com/drivers).

DIMENSIONS



SPECIFYING CODE

FIXTURE CODE	FINISH	COLOR TEMPERATURE	DRIVER	CERTIFICATION
SH - S - 8.1				For indoor use only.
	<p>SB - Satin Brass</p> <p>BB - Blackened Brass</p> <p>AB - Antique Brass</p> <p>SN - Satin Nickel</p> <p>PN - Polished Nickel</p> <p>SC - Satin Copper</p>	<p>18 - 1800K</p> <p>20 - 2000K</p> <p>24 - 2400K</p> <p>27 - 2700K</p> <p>30 - 3000K</p> <p>35 - 3500K</p> <p>42 - 4200K</p> <p>50 - 5000K</p>	<p>UNI - Universal Remote MLV/ELV/010V (120-277V)</p> <p>MK - MikroDim (120V)</p> <p>SW - Switchex (120V)</p> <p>For more info, visit lukelampco.com/drivers</p>	<p>DR - UL Dry (Indoor)</p> <p>DM - UL Damp (Indoor)</p> <p>CR - CE Dry (Indoor)*</p> <p>CM - CE Damp (Indoor)*</p> <p>* If CE is specified, we cannot supply the drivers.</p>